
PyHamcrest Documentation

Release 2.0.0

hamcrest.org

Jan 16, 2020

Contents

1	PyHamcrest Tutorial	3
2	Writing Custom Matchers	7
3	Matcher Library	9
4	Integration with PyUnit and Other Libraries	33
5	Core API	35
6	Indices and tables	41
	Python Module Index	43
	Index	45

Contents:

1.1 Introduction

PyHamcrest is a framework for writing matcher objects, allowing you to declaratively define “match” rules. There are a number of situations where matchers are invaluable, such as UI validation, or data filtering, but it is in the area of writing flexible tests that matchers are most commonly used. This tutorial shows you how to use PyHamcrest for unit testing.

When writing tests it is sometimes difficult to get the balance right between overspecifying the test (and making it brittle to changes), and not specifying enough (making the test less valuable since it continues to pass even when the thing being tested is broken). Having a tool that allows you to pick out precisely the aspect under test and describe the values it should have, to a controlled level of precision, helps greatly in writing tests that are “just right.” Such tests fail when the behavior of the aspect under test deviates from the expected behavior, yet continue to pass when minor, unrelated changes to the behaviour are made.

1.2 My first PyHamcrest test

We'll start by writing a very simple PyUnit test, but instead of using PyUnit's `assertEqual` method, we'll use PyHamcrest's `assert_that` construct and the standard set of matchers:

```
from hamcrest import *
import unittest

class BiscuitTest(unittest.TestCase):
    def testEquals(self):
        theBiscuit = Biscuit('Ginger')
        myBiscuit = Biscuit('Ginger')
        assert_that(theBiscuit, equal_to(myBiscuit))

if __name__ == '__main__':
    unittest.main()
```

The `assert_that` function is a stylized sentence for making a test assertion. In this example, the subject of the assertion is the object `theBiscuit`, which is the first method parameter. The second method parameter is a matcher for `Biscuit` objects, here a matcher that checks one object is equal to another using the Python `==` operator. The test passes since the `Biscuit` class defines an `__eq__` method.

If you have more than one assertion in your test you can include an identifier for the tested value in the assertion:

```
assert_that(theBiscuit.getChocolateChipCount(), equal_to(10), 'chocolate chips')
assert_that(theBiscuit.getHazelnutCount(), equal_to(3), 'hazelnuts')
```

As a convenience, `assert_that` can also be used to verify a boolean condition:

```
assert_that(theBiscuit.isCooked(), 'cooked')
```

This is equivalent to the `assert_` method of `unittest.TestCase`, but because it's a standalone function, it offers greater flexibility in test writing.

1.3 Asserting Exceptions

There's a utility function and matcher available to help you test that your code has the expected behavior in situations where it should raise an exception. The `calling` function wraps a callable, and then allows you to set arguments to be used in a call to the wrapped callable. This, together with the `raises` matcher lets you assert that calling a method with certain arguments causes an exception to be thrown. It is also possible to provide a regular expression pattern to the `raises` matcher allowing you assure that the right issue was found:

```
assert_that(calling(parse, bad_data), raises(ValueError))

assert_that(calling(translate).with_(curse_words), raises(LanguageError, "\w+very_\u2192naughty"))

assert_that(broken_function, raises(Exception))

# This will fail and complain that 23 is not callable
# assert_that(23, raises(IOError))
```

1.4 Predefined matchers

PyHamcrest comes with a library of useful matchers:

- Object
 - `equal_to` - match equal object
 - `has_length` - match `len(item)`
 - `has_property` - match value of property with given name
 - `has_properties` - match an object that has all of the given properties.
 - `has_string` - match `str(item)`
 - `instance_of` - match object type
 - `none, not_none` - match `None`, or not `None`
 - `same_instance` - match same object

- *calling*, *raises* - wrap a method call and assert that it raises an exception
- Number
 - *close_to* - match number close to a given value
 - *greater_than*, *greater_than_or_equal_to*, *less_than*, *less_than_or_equal_to* - match numeric ordering
- Text
 - *contains_string* - match part of a string
 - *ends_with* - match the end of a string
 - *equal_to_ignoring_case* - match the complete string but ignore case
 - *equal_to_ignoring_whitespace* - match the complete string but ignore extra whitespace
 - *starts_with* - match the beginning of a string
 - *string_contains_in_order* - match parts of a string, in relative order
- Logical
 - *all_of* - and together all matchers
 - *any_of* - or together all matchers
 - *anything* - match anything, useful in composite matchers when you don't care about a particular value
 - *is_not* - negate the matcher
 - *not_* - alias of *is_not* for better readability of negations.
- Sequence
 - *contains* - exactly match the entire sequence
 - *contains_inanyorder* - match the entire sequence, but in any order
 - *has_item* - match if given item appears in the sequence
 - *has_items* - match if all given items appear in the list, in any order
 - *is_in* - match if item appears in the given sequence
 - *only_contains* - match if sequence's items appear in given list
 - *empty* - match if the sequence is empty
- Dictionary
 - *has_entries* - match dictionary with list of key-value pairs
 - *has_entry* - match dictionary containing a key-value pair
 - *has_key* - match dictionary with a key
 - *has_value* - match dictionary with a value
- Decorator
 - *described_as* - give the matcher a custom failure description
 - *is_* - decorator to improve readability - see *Syntactic sugar*, below

The arguments for many of these matchers accept not just a matching value, but another matcher, so matchers can be composed for greater flexibility. For example, `only_contains(less_than(5))` will match any sequence where every item is less than 5.

1.5 Syntactic sugar

PyHamcrest strives to make your tests as readable as possible. For example, the `is_` matcher is a wrapper that doesn't add any extra behavior to the underlying matcher. The following assertions are all equivalent:

```
assert_that(theBiscuit, equal_to(myBiscuit))
assert_that(theBiscuit, is_(equal_to(myBiscuit)))
assert_that(theBiscuit, is_(myBiscuit))
```

The last form is allowed since `is_(value)` wraps most non-matcher arguments with `equal_to`. But if the argument is a type, it is wrapped with `instance_of`, so the following are also equivalent:

```
assert_that(theBiscuit, instance_of(Biscuit))
assert_that(theBiscuit, is_(instance_of(Biscuit)))
assert_that(theBiscuit, is_(Biscuit))
```

(Note that PyHamcrest's `is_` matcher is unrelated to Python's `is` operator. The matcher for object identity is `same_instance`.)

Writing Custom Matchers

PyHamcrest comes bundled with lots of useful matchers, but you'll probably find that you need to create your own from time to time to fit your testing needs. This commonly occurs when you find a fragment of code that tests the same set of properties over and over again (and in different tests), and you want to bundle the fragment into a single assertion. By writing your own matcher you'll eliminate code duplication and make your tests more readable!

Let's write our own matcher for testing if a calendar date falls on a Saturday. This is the test we want to write:

```
def testDateIsOnASaturday(self):
    d = datetime.date(2008, 04, 26)
    assert_that(d, is_(on_a_saturday()))
```

And here's the implementation:

```
from hamcrest.core.base_matcher import BaseMatcher
from hamcrest.core.helpers.hasmethod import hasmethod

class IsGivenDayOfWeek(BaseMatcher):

    def __init__(self, day):
        self.day = day # Monday is 0, Sunday is 6

    def _matches(self, item):
        if not hasmethod(item, 'weekday'):
            return False
        return item.weekday() == self.day

    def describe_to(self, description):
        day_as_string = ['Monday', 'Tuesday', 'Wednesday', 'Thursday',
                        'Friday', 'Saturday', 'Sunday']
        description.append_text('calendar date falling on ') \
            .append_text(day_as_string[self.day])

def on_a_saturday():
    return IsGivenDayOfWeek(5)
```

For our `Matcher` implementation we implement the `_matches` method - which calls the `weekday` method after confirming that the argument (which may not be a date) has such a method - and the `describe_to` method - which is used to produce a failure message when a test fails. Here's an example of how the failure message looks:

```
assert_that(datetime.date(2008, 04, 06), is_(on_a_saturday()))
```

fails with the message:

```
AssertionError:
Expected: is calendar date falling on Saturday
got: <2008-04-06>
```

Let's say this matcher is saved in a module named `isgivendayofweek`. We could use it in our test by importing the factory function `on_a_saturday`:

```
from hamcrest import *
import unittest
from isgivendayofweek import on_a_saturday

class DateTest(unittest.TestCase):
    def testDateIsOnASaturday(self):
        d = datetime.date(2008, 04, 26)
        assert_that(d, is_(on_a_saturday()))

if __name__ == '__main__':
    unittest.main()
```

Even though the `on_a_saturday` function creates a new matcher each time it is called, you should not assume this is the only usage pattern for your matcher. Therefore you should make sure your matcher is stateless, so a single instance can be reused between matches.

If you need your matcher to provide more details in case of a mismatch, you can override the `describe_mismatch` method. For example, if we added this `describe_mismatch` implementation to our `IsGivenDayOfWeek` matcher:

```
def describe_mismatch(self, item, mismatch_description):
    day_as_string = ['Monday', 'Tuesday', 'Wednesday', 'Thursday',
                    'Friday', 'Saturday', 'Sunday']
    mismatch_description.append_text('got ') \
        .append_description_of(item) \
        .append_text(' which is a ') \
        .append_text(day_as_string[item.weekday()])
```

Our matcher would now give the message:

```
AssertionError:
Expected: is calendar date falling on Saturday
got: <2008-04-06> which is a Sunday
```

Occasionally, you might also need your matcher to explain why it matched successfully. For example, if your matcher is wrapped by a `is_not` matcher, the `is_not` matcher can only explain its mismatches by understanding why your matcher succeeded. In this case, your matcher can implement `describe_match`.

Library of Matcher implementations.

3.1 Object Matchers

Matchers that inspect objects.

3.1.1 `equal_to`

class `hamcrest.core.core.isequal.IsEqual` (*equals: Any*)

Bases: `hamcrest.core.base_matcher.BaseMatcher`

describe_to (*description: hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters *description* – The description to be built or appended to.

`hamcrest.core.core.isequal.equal_to` (*obj: Any*) → `hamcrest.core.matcher.Matcher[typing.Any][Any]`

Matches if object is equal to a given object.

Parameters *obj* – The object to compare against as the expected value.

This matcher compares the evaluated object to `obj` for equality.

3.1.2 `has_length`

class `hamcrest.library.object.haslength.HasLength` (*len_matcher: hamcrest.core.matcher.Matcher[int][int]*)

Bases: `hamcrest.core.base_matcher.BaseMatcher`

describe_mismatch (*item:* *collections.abc.Sized*, *mismatch_description:* *hamcrest.core.description.Description*) → None

Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches(item)` is `False`, but will not check this.

Parameters

- **item** – The item that the *Matcher* has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to (*description:* *hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters description – The description to be built or appended to.

`hamcrest.library.object.haslength.has_length` (*match:* *Union[int, hamcrest.core.matcher.Matcher[int][int]]*) → *hamcrest.core.matcher.Matcher[collections.abc.Sized][collections.abc.Sized]*

Matches if `len(item)` satisfies a given matcher.

Parameters match – The matcher to satisfy, or an expected value for *equal_to* matching.

This matcher invokes the `len` function on the evaluated object to get its length, passing the result to a given matcher for evaluation.

If the `match` argument is not a matcher, it is implicitly wrapped in an *equal_to* matcher to check for equality.

Examples:

```
has_length(greater_than(6))
has_length(5)
```

3.1.3 has_string

class `hamcrest.library.object.hasstring.HasString` (*str_matcher:* *hamcrest.core.matcher.Matcher[str][str]*)

Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_to (*description:* *hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters description – The description to be built or appended to.

`hamcrest.library.object.hasstring.has_string` (*match:* *hamcrest.core.matcher.Matcher[object][object]*) → *hamcrest.core.matcher.Matcher[object][object]*

Matches if `str(item)` satisfies a given matcher.

Parameters match – The matcher to satisfy, or an expected value for *equal_to* matching.

This matcher invokes the `str` function on the evaluated object to get its length, passing the result to a given matcher for evaluation. If the `match` argument is not a matcher, it is implicitly wrapped in an *equal_to* matcher to check for equality.

Examples:

```
has_string(starts_with('foo'))
has_string('bar')
```

3.1.4 has_properties/has_property

class hamcrest.library.object.hasproperty.**IsObjectWithProperty** (*property_name:*
str,
value_matcher:
ham-
crest.core.matcher.Matcher[~V][V])

Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_mismatch (*item: object, mismatch_description: hamcrest.core.description.Description*)
 → None

Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches(item)` is `False`, but will not check this.

Parameters

- **item** – The item that the *Matcher* has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to (*description: hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters description – The description to be built or appended to.

hamcrest.library.object.hasproperty.**has_properties** (**keys_valuemarkers, **kv_args*)

Matches if an object has properties satisfying all of a dictionary of string property names and corresponding value matchers.

Parameters matcher_dict – A dictionary mapping keys to associated value matchers, or to expected values for *equal_to* matching.

Note that the keys must be actual keys, not matchers. Any value argument that is not a matcher is implicitly wrapped in an *equal_to* matcher to check for equality.

Examples:

```
has_properties({'foo':equal_to(1), 'bar':equal_to(2)})
has_properties({'foo':1, 'bar':2})
```

`has_properties` also accepts a list of keyword arguments:

```
hamcrest.library.object.hasproperty.has_properties (keyword1=value_matcher1[,
                                                    keyword2=value_matcher2[,
                                                    ...]])
```

Parameters

- **keyword1** – A keyword to look up.
- **valueMatcher1** – The matcher to satisfy for the value, or an expected value for *equal_to* matching.

Examples:

```
has_properties(foo=equal_to(1), bar=equal_to(2))
has_properties(foo=1, bar=2)
```

Finally, `has_properties` also accepts a list of alternating keys and their value matchers:

```
hamcrest.library.object.hasproperty.has_properties(key1, value_matcher1[, ...])
```

Parameters

- **key1** – A key (not a matcher) to look up.
- **valueMatcher1** – The matcher to satisfy for the value, or an expected value for `equal_to` matching.

Examples:

```
has_properties('foo', equal_to(1), 'bar', equal_to(2))
has_properties('foo', 1, 'bar', 2)
```

```
hamcrest.library.object.hasproperty.has_property(name: str, match: Union[None, hamcrest.core.matcher.Matcher[~V][V], V] = None) → hamcrest.core.matcher.Matcher[object][object]
```

Matches if object has a property with a given name whose value satisfies a given matcher.

Parameters

- **name** – The name of the property.
- **match** – Optional matcher to satisfy.

This matcher determines if the evaluated object has a property with a given name. If no such property is found, `has_property` is not satisfied.

If the property is found, its value is passed to a given matcher for evaluation. If the `match` argument is not a matcher, it is implicitly wrapped in an `equal_to` matcher to check for equality.

If the `match` argument is not provided, the `anything` matcher is used so that `has_property` is satisfied if a matching property is found.

Examples:

```
has_property('name', starts_with('J'))
has_property('name', 'Jon')
has_property('name')
```

3.1.5 instance_of

```
class hamcrest.core.core.isinstanceof.IsInstanceOf(expected_type: Type[CT_co])
```

Bases: `hamcrest.core.base_matcher.BaseMatcher`

```
describe_to(description: hamcrest.core.description.Description) → None
```

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.


```
hamcrest.core.core.isinstanceof.instance_of (atype:      Type[CT_co]) → hamcrest.core.matcher.Matcher[object][object]
```

Matches if object is an instance of, or inherits from, a given type.

Parameters *atype* – The type to compare against as the expected type.

This matcher checks whether the evaluated object is an instance of *atype* or an instance of any class that inherits from *atype*.

Example:

```
instance_of(str)
```

3.1.6 none, not_none

```
class hamcrest.core.core.isnone.IsNone
```

Bases: *hamcrest.core.base_matcher.BaseMatcher*

```
describe_to (description: hamcrest.core.description.Description) → None
```

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters *description* – The description to be built or appended to.

```
hamcrest.core.core.isnone.none () → hamcrest.core.matcher.Matcher[typing.Union[typing.Any, NoneType]][Optional[Any]]
```

Matches if object is None.

```
hamcrest.core.core.isnone.not_none () → hamcrest.core.matcher.Matcher[typing.Union[typing.Any, NoneType]][Optional[Any]]
```

Matches if object is not None.

3.1.7 same_instance

```
class hamcrest.core.core.issame.IsSame (obj: T)
```

Bases: *hamcrest.core.base_matcher.BaseMatcher*

```
describe_mismatch (item: T, mismatch_description: hamcrest.core.description.Description) → None
```

Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches(item)` is `False`, but will not check this.

Parameters

- *item* – The item that the *Matcher* has rejected.
- *mismatch_description* – The description to be built or appended to.

```
describe_to (description: hamcrest.core.description.Description) → None
```

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters *description* – The description to be built or appended to.

`hamcrest.core.core.issame.same_instance` (*obj*: *T*) → `hamcrest.core.matcher.Matcher[~T][T]`
Matches if evaluated object is the same instance as a given object.

Parameters *obj* – The object to compare against as the expected value.

This matcher invokes the `is` identity operator to determine if the evaluated object is the the same object as *obj*.

3.1.8 calling, raises

class `hamcrest.core.core.raises.Raises` (*expected*: *Exception*, *pattern*: *Optional[str]* = *None*, *matching*: *Optional[hamcrest.core.matcher.Matcher]* = *None*)
Bases: `hamcrest.core.base_matcher.BaseMatcher`

describe_match (*item*, *match_description*: `hamcrest.core.description.Description`) → *None*
Generates a description of why the matcher has accepted the item.

The description may be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches(item)` is `True`, but will not check this.

Parameters

- **item** – The item that the `Matcher` has accepted.
- **match_description** – The description to be built or appended to.

describe_mismatch (*item*, *description*: `hamcrest.core.description.Description`) → *None*
Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches(item)` is `False`, but will not check this.

Parameters

- **item** – The item that the `Matcher` has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to (*description*: `hamcrest.core.description.Description`) → *None*
Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters *description* – The description to be built or appended to.

`hamcrest.core.core.raises.calling` (*func*: *Callable[...]*, *Any*) → `hamcrest.core.raises.DeferredCallable`
Wrapper for function call that delays the actual execution so that `raises` matcher can catch any thrown exception.

Parameters *func* – The function or method to be called

The arguments can be provided with a call to the `with_args` function on the returned object:

```
calling(my_method).with_args(arguments, and_='keywords')
```

`hamcrest.core.core.raises.raises` (*exception*: *Exception*, *pattern*=*None*, *matching*=*None*)
→ `hamcrest.core.matcher.Matcher[typing.Callable[...], typing.Any][Callable[...], Any]`

Matches if the called function raised the expected exception.

Parameters

- **exception** – The class of the expected exception
- **pattern** – Optional regular expression to match exception message.
- **matching** – Optional Hamcrest matchers to apply to the exception.

Expects the actual to be wrapped by using `calling`, or a callable taking no arguments. Optional argument `pattern` should be a string containing a regular expression. If provided, the string representation of the actual exception - e.g. `str(actual)` - must match `pattern`.

Examples:

```
assert_that(calling(int).with_args('q'), raises(TypeError))
assert_that(calling(parse, broken_input), raises(ValueError))
assert_that(
    calling(valid_user, bad_json),
    raises(HTTPError, matching=has_properties(status_code=500))
)
```

3.2 Number Matchers

Matchers that perform numeric comparisons.

3.2.1 close_to

class `hamcrest.library.number.iscloseto.IsCloseTo` (*value: Union[float, decimal.Decimal], delta: Union[float, decimal.Decimal]*)

Bases: `hamcrest.core.base_matcher.BaseMatcher`

describe_mismatch (*item: Union[float, decimal.Decimal], mismatch_description: hamcrest.core.description.Description*) → None

Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches(item)` is False, but will not check this.

Parameters

- **item** – The item that the *Matcher* has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to (*description: hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters description – The description to be built or appended to.

`hamcrest.library.number.iscloseto.close_to` (*value, delta*)

Matches if object is a number close to a given value, within a given delta.

Parameters

- **value** – The value to compare against as the expected value.
- **delta** – The maximum delta between the values for which the numbers are considered close.

This matcher compares the evaluated object against `value` to see if the difference is within a positive `delta`.

Example:

```
close_to(3.0, 0.25)
```

`hamcrest.library.number.iscloseto.isnumeric` (*value: Any*) → bool

Confirm that ‘value’ can be treated numerically; duck-test accordingly

3.2.2 greater_than, greater_than_or_equal_to, less_than, less_than_or_equal_to

```
class hamcrest.library.number.ordering_comparison.OrderingComparison (value:
                                                                    Any,
                                                                    com-
                                                                    pari-
                                                                    son_function:
                                                                    Callable[[Any,
                                                                    Any],
                                                                    bool],
                                                                    com-
                                                                    pari-
                                                                    son_description:
                                                                    str)
```

Bases: `hamcrest.core.base_matcher.BaseMatcher`

describe_to (*description: hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

`hamcrest.library.number.ordering_comparison.greater_than` (*value: Any*) → `hamcrest.core.matcher.Matcher[typing.Any][Any]`

Matches if object is greater than a given value.

Parameters **value** – The value to compare against.

`hamcrest.library.number.ordering_comparison.greater_than_or_equal_to` (*value: Any*) → `hamcrest.core.matcher.Matcher[typing.Any][Any]`

Matches if object is greater than or equal to a given value.

Parameters **value** – The value to compare against.

`hamcrest.library.number.ordering_comparison.less_than` (*value: Any*) → `hamcrest.core.matcher.Matcher[typing.Any][Any]`

Matches if object is less than a given value.

Parameters **value** – The value to compare against.

`hamcrest.library.number.ordering_comparison.less_than_or_equal_to` (*value: Any*) → `hamcrest.core.matcher.Matcher[typing.Any][Any]`

Matches if object is less than or equal to a given value.

Parameters *value* – The value to compare against.

3.3 Text Matchers

Matchers that perform text comparisons.

3.3.1 contains_string

```
class hamcrest.library.text.stringcontains.StringContains (substring)
    Bases: hamcrest.library.text.substringmatcher.SubstringMatcher
hamcrest.library.text.stringcontains.contains_string (substring: str) → hamcrest.core.matcher.Matcher[str][str]
```

Matches if object is a string containing a given string.

Parameters *string* – The string to search for.

This matcher first checks whether the evaluated object is a string. If so, it checks whether it contains *string*.

Example:

```
contains_string("def")
```

will match “abcdefg”.

3.3.2 ends_with

```
class hamcrest.library.text.stringendswith.StringEndsWith (substring)
    Bases: hamcrest.library.text.substringmatcher.SubstringMatcher
hamcrest.library.text.stringendswith.ends_with (string: str) → hamcrest.core.matcher.Matcher[str][str]
```

Matches if object is a string ending with a given string.

Parameters *string* – The string to search for.

This matcher first checks whether the evaluated object is a string. If so, it checks if *string* matches the ending characters of the evaluated object.

Example:

```
ends_with("bar")
```

will match “foobar”.

3.3.3 equal_to_ignoring_case

```
class hamcrest.library.text.isequal_ignoring_case.IsEqualIgnoringCase (string: str)
    Bases: hamcrest.core.base_matcher.BaseMatcher
```

```
describe_to (description: hamcrest.core.description.Description) → None
```

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

```
hamcrest.library.text.isequal_ignoring_case.equal_to_ignoring_case (string:  
                                                                    str)
```

→ ham-

crest.core.matcher.Matcher[str][str]

Matches if object is a string equal to a given string, ignoring case differences.

Parameters **string** – The string to compare against as the expected value.

This matcher first checks whether the evaluated object is a string. If so, it compares it with `string`, ignoring differences of case.

Example:

```
equal_to_ignoring_case("hello world")
```

will match “heLLo WorlD”.

3.3.4 equal_to_ignoring_whitespace

```
class hamcrest.library.text.isequal_ignoring_whitespace.IsEqualIgnoringWhiteSpace (string)  
    Bases: hamcrest.core.base_matcher.BaseMatcher
```

```
describe_to (description: hamcrest.core.description.Description) → None
```

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

```
hamcrest.library.text.isequal_ignoring_whitespace.equal_to_ignoring_whitespace (string:  
                                                                    str)
```

→

ham-

crest.core.matcher.Matcher[str][str]

Matches if object is a string equal to a given string, ignoring differences in whitespace.

Parameters **string** – The string to compare against as the expected value.

This matcher first checks whether the evaluated object is a string. If so, it compares it with `string`, ignoring differences in runs of whitespace.

Example:

```
equal_to_ignoring_whitespace("hello world")
```

will match "hello world".

3.3.5 matches_regexp

```
class hamcrest.library.text.stringmatches.StringMatchesPattern (pattern)  
    Bases: hamcrest.core.base_matcher.BaseMatcher
```

```
describe_to (description: hamcrest.core.description.Description) → None
```

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters description – The description to be built or appended to.

```
hamcrest.library.text.stringmatches.matches_regexp (pattern: Union[str, Pattern[str]]) → hamcrest.core.matcher.Matcher[str][str]
```

Matches if object is a string containing a match for a given regular expression.

Parameters pattern – The regular expression to search for.

This matcher first checks whether the evaluated object is a string. If so, it checks if the regular expression `pattern` matches anywhere within the evaluated object.

3.3.6 starts_with

```
class hamcrest.library.text.stringstartswith.StringStartsWith (substring)
```

Bases: `hamcrest.library.text.substringmatcher.SubstringMatcher`

```
hamcrest.library.text.stringstartswith.starts_with (substring: str) → hamcrest.core.matcher.Matcher[str][str]
```

Matches if object is a string starting with a given string.

Parameters string – The string to search for.

This matcher first checks whether the evaluated object is a string. If so, it checks if `string` matches the beginning characters of the evaluated object.

Example:

```
starts_with("foo")
```

will match “foobar”.

3.3.7 string_contains_in_order

```
class hamcrest.library.text.stringcontainsinorder.StringContainsInOrder (*substrings)
```

Bases: `hamcrest.core.base_matcher.BaseMatcher`

```
describe_to (description: hamcrest.core.description.Description) → None
```

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters description – The description to be built or appended to.

```
hamcrest.library.text.stringcontainsinorder.string_contains_in_order (string1[, string2[, ...]])
```

Matches if object is a string containing a given list of substrings in relative order.

Parameters string1, .. – A comma-separated list of strings.

This matcher first checks whether the evaluated object is a string. If so, it checks whether it contains a given list of strings, in relative order to each other. The searches are performed starting from the beginning of the evaluated string.

Example:

```
string_contains_in_order("bc", "fg", "jkl")
```

will match “abcdefghijklm”.

3.4 Logical Matchers

Boolean logic using other matchers.

3.4.1 all_of

class hamcrest.core.core.allof.**Allof**(*matchers, **kwargs)

Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_mismatch(item: T, mismatch_description: hamcrest.core.description.Description) → None

Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches(item)` is `False`, but will not check this.

Parameters

- **item** – The item that the *Matcher* has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to(description: hamcrest.core.description.Description) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

matches(item: T, mismatch_description: Optional[hamcrest.core.description.Description] = None) → bool

Evaluates the matcher for argument item.

If a mismatch is detected and argument `mismatch_description` is provided, it will generate a description of why the matcher has not accepted the item.

Parameters

- **item** – The object against which the matcher is evaluated.
- **mismatch_description** –

Returns `True` if item matches, otherwise `False`.

hamcrest.core.core.allof.**all_of**(matcher1[, matcher2[, ...]])

Matches if all of the given matchers evaluate to `True`.

Parameters **matcher1, ..** – A comma-separated list of matchers.

The matchers are evaluated from left to right using short-circuit evaluation, so evaluation stops as soon as a matcher returns `False`.

Any argument that is not a matcher is implicitly wrapped in an *equal_to* matcher to check for equality.

3.4.2 any_of

class hamcrest.core.core.anyof.**AnyOf** (*matchers)

Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_to (description: *hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

hamcrest.core.core.anyof.**any_of** (matcher1[, matcher2[, ...]])

Matches if any of the given matchers evaluate to True.

Parameters **matcher1**, .. – A comma-separated list of matchers.

The matchers are evaluated from left to right using short-circuit evaluation, so evaluation stops as soon as a matcher returns True.

Any argument that is not a matcher is implicitly wrapped in an *equal_to* matcher to check for equality.

3.4.3 anything

class hamcrest.core.core.isanything.**IsAnything** (description: *Optional[str]*)

Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_to (description: *hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

hamcrest.core.core.isanything.**anything** ([description])

Matches anything.

Parameters **description** – Optional string used to describe this matcher.

This matcher always evaluates to True. Specify this in composite matchers when the value of a particular element is unimportant.

3.4.4 is_not

class hamcrest.core.core.isnot.**IsNot** (matcher: *hamcrest.core.matcher.Matcher[~T][T]*)

Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_mismatch (item: *T*, mismatch_description: *hamcrest.core.description.Description*) →

None

Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that *matches(item)* is False, but will not check this.

Parameters

- **item** – The item that the *Matcher* has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to (*description*: *hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters *description* – The description to be built or appended to.

`hamcrest.core.core.isnot.is_not` (*match*)

Inverts the given matcher to its logical negation.

Parameters *match* – The matcher to negate.

This matcher compares the evaluated object to the negation of the given matcher. If the `match` argument is not a matcher, it is implicitly wrapped in an `equal_to` matcher to check for equality, and thus matches for inequality.

Examples:

```
assert_that(cheese, is_not(equal_to(smelly)))
assert_that(cheese, is_not(smelly))
```

`hamcrest.core.core.isnot.not_` (*match*: *Union[hamcrest.core.matcher.Matcher[~T][T], T]*) → *hamcrest.core.matcher.Matcher[~T][T]*

Alias of `is_not` for better readability of negations.

Examples:

```
assert_that(alist, not_(has_item(item)))
```

3.5 Sequence Matchers

Matchers of sequences.

3.5.1 contains_exactly

class `hamcrest.library.collection.issequence_containinginorder.IsSequenceContainingInOrder`

Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_mismatch (*item*: *Sequence[T]*, *mismatch_description*: *hamcrest.core.description.Description*) → None

Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches(item)` is `False`, but will not check this.

Parameters

- **item** – The item that the *Matcher* has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to (*description*: *hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

matches (*item*: *Sequence*[*T*], *mismatch_description*: *Optional*[*hamcrest.core.description.Description*] = *None*) → bool

Evaluates the matcher for argument *item*.

If a mismatch is detected and argument *mismatch_description* is provided, it will generate a description of why the matcher has not accepted the item.

Parameters

- **item** – The object against which the matcher is evaluated.
- **mismatch_description** –

Returns True if *item* matches, otherwise False.

```
hamcrest.library.collection.issequence_containinginorder.contains_exactly (match1[,
                                                                    match2[,
                                                                    ...
                                                                    ]
                                                                    ])
```

Matches if sequence's elements satisfy a given list of matchers, in order.

Parameters **match1**, .. – A comma-separated list of matchers.

This matcher iterates the evaluated sequence and a given list of matchers, seeing if each element satisfies its corresponding matcher.

Any argument that is not a matcher is implicitly wrapped in an *equal_to* matcher to check for equality.

3.5.2 contains_inanyorder

```
class hamcrest.library.collection.issequence_containinginanyorder.IsSequenceContainingInAny
```

Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_mismatch (*item*: *Sequence*[*T*], *mismatch_description*: *hamcrest.core.description.Description*) → None

Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that *matches* (*item*) is False, but will not check this.

Parameters

- **item** – The item that the *Matcher* has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to (*description*: *hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

matches (*item*: *Sequence*[*T*], *mismatch_description*: *Optional*[*hamcrest.core.description.Description*] = *None*) → bool

Evaluates the matcher for argument *item*.

If a mismatch is detected and argument `mismatch_description` is provided, it will generate a description of why the matcher has not accepted the item.

Parameters

- **item** – The object against which the matcher is evaluated.
- **mismatch_description** –

Returns True if `item` matches, otherwise False.

```
hamcrest.library.collection.issequence_containinginanyorder.contains_inanyorder (match1[,  
match2[,  
...  
])
```

Matches if sequences's elements, in any order, satisfy a given list of matchers.

Parameters `match1, ..` – A comma-separated list of matchers.

This matcher iterates the evaluated sequence, seeing if each element satisfies any of the given matchers. The matchers are tried from left to right, and when a satisfied matcher is found, it is no longer a candidate for the remaining elements. If a one-to-one correspondence is established between elements and matchers, `contains_inanyorder` is satisfied.

Any argument that is not a matcher is implicitly wrapped in an `equal_to` matcher to check for equality.

3.5.3 has_item, has_items

```
class hamcrest.library.collection.issequence_containing.IsSequenceContaining (element_matcher:  
hamcrest.core.matcher.Matcher)
```

Bases: `hamcrest.core.base_matcher.BaseMatcher`

describe_to (*description: hamcrest.core.description.Description*) → None
Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

```
class hamcrest.library.collection.issequence_containing.IsSequenceContainingEvery (*element_matchers:  
hamcrest.core.matcher.Matcher)
```

describe_mismatch (*item: Sequence[T], mismatch_description: hamcrest.core.description.Description*) → None
Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches(item)` is False, but will not check this.

Parameters

- **item** – The item that the `Matcher` has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to (*description: hamcrest.core.description.Description*) → None
Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters description – The description to be built or appended to.

```
hamcrest.library.collection.issequence_containing.has_item (match: Union[T, hamcrest.core.matcher.Matcher[~T][T]])
→ hamcrest.core.matcher.Matcher[typing.Sequence[~T]]
```

Matches if any element of sequence satisfies a given matcher.

Parameters match – The matcher to satisfy, or an expected value for `equal_to` matching.

This matcher iterates the evaluated sequence, searching for any element that satisfies a given matcher. If a matching element is found, `has_item` is satisfied.

If the `match` argument is not a matcher, it is implicitly wrapped in an `equal_to` matcher to check for equality.

```
hamcrest.library.collection.issequence_containing.has_items (match1[, match2[, ...]])
```

Matches if all of the given matchers are satisfied by any elements of the sequence.

Parameters match1, .. – A comma-separated list of matchers.

This matcher iterates the given matchers, searching for any elements in the evaluated sequence that satisfy them. If each matcher is satisfied, then `has_items` is satisfied.

Any argument that is not a matcher is implicitly wrapped in an `equal_to` matcher to check for equality.

3.5.4 is_in

```
class hamcrest.library.collection.isin.IsIn (sequence: Sequence[T])
```

Bases: `hamcrest.core.base_matcher.BaseMatcher`

```
describe_to (description: hamcrest.core.description.Description) → None
```

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters description – The description to be built or appended to.

```
hamcrest.library.collection.isin.is_in (sequence: Sequence[T]) → hamcrest.core.matcher.Matcher[~T][T]
```

Matches if evaluated object is present in a given sequence.

Parameters sequence – The sequence to search.

This matcher invokes the `in` membership operator to determine if the evaluated object is a member of the sequence.

3.5.5 only_contains

```
class hamcrest.library.collection.issequence_onlycontaining.IsSequenceOnlyContaining (matcher)
```

`hamcrest.co`

Bases: `hamcrest.core.base_matcher.BaseMatcher`

```
describe_to (description: hamcrest.core.description.Description) → None
```

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters *description* – The description to be built or appended to.

`hamcrest.library.collection.issequence_onlycontaining.only_contains` (*match1* [*match2*, ...]])

Matches if each element of sequence satisfies any of the given matchers.

Parameters *match1*, ... – A comma-separated list of matchers.

This matcher iterates the evaluated sequence, confirming whether each element satisfies any of the given matchers.

Example:

```
only_contains(less_than(4))
```

will match `[3, 1, 2]`.

Any argument that is not a matcher is implicitly wrapped in an `equal_to` matcher to check for equality.

3.5.6 empty

class `hamcrest.library.collection.is_empty.IsEmpty`

Bases: `hamcrest.core.base_matcher.BaseMatcher`

describe_to (*description*: `hamcrest.core.description.Description`) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters *description* – The description to be built or appended to.

matches (*item*: *Sized*, *mismatch_description*: *Optional*[`hamcrest.core.description.Description`] = None) → bool

Evaluates the matcher for argument *item*.

If a mismatch is detected and argument *mismatch_description* is provided, it will generate a description of why the matcher has not accepted the item.

Parameters

- **item** – The object against which the matcher is evaluated.
- **mismatch_description** –

Returns True if *item* matches, otherwise False.

`hamcrest.library.collection.is_empty.empty()`

This matcher matches any collection-like object that responds to the `__len__` method, and has a length of 0.

3.6 Dictionary Matchers

Matchers of dictionaries.

3.6.1 has_entries

class `hamcrest.library.collection.isdict_containingentries.IsDictContainingEntries` (*value_mate*

Bases: `hamcrest.core.base_matcher.BaseMatcher`

describe_keyvalue (*index: int, value: V, description: hamcrest.core.description.Description*) → None
Describes key-value pair at given index.

describe_mismatch (*item: Mapping[K, V], mismatch_description: hamcrest.core.description.Description*) → None
Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches(item)` is `False`, but will not check this.

Parameters

- **item** – The item that the *Matcher* has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to (*description: hamcrest.core.description.Description*) → None
Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters description – The description to be built or appended to.

matches (*item: Mapping[K, V], mismatch_description: Optional[hamcrest.core.description.Description]*
= None) → bool
Evaluates the matcher for argument item.

If a mismatch is detected and argument `mismatch_description` is provided, it will generate a description of why the matcher has not accepted the item.

Parameters

- **item** – The object against which the matcher is evaluated.
- **mismatch_description** –

Returns True if item matches, otherwise False.

`hamcrest.library.collection.isdict_containingentries.has_entries(matcher_dict)`
Matches if dictionary contains entries satisfying a dictionary of keys and corresponding value matchers.

Parameters matcher_dict – A dictionary mapping keys to associated value matchers, or to expected values for `equal_to` matching.

Note that the keys must be actual keys, not matchers. Any value argument that is not a matcher is implicitly wrapped in an `equal_to` matcher to check for equality.

Examples:

```
has_entries({'foo':equal_to(1), 'bar':equal_to(2)})
has_entries({'foo':1, 'bar':2})
```

`has_entries` also accepts a list of keyword arguments:

```
hamcrest.library.collection.isdict_containingentries.has_entries(keyword1=value_matcher1[,
                                                                    key-
                                                                    word2=value_matcher2[,
                                                                    ...]])
```

Parameters

- **keyword1** – A keyword to look up.

- **valueMatcher1** – The matcher to satisfy for the value, or an expected value for *equal_to* matching.

Examples:

```
has_entries(foo=equal_to(1), bar=equal_to(2))
has_entries(foo=1, bar=2)
```

Finally, `has_entries` also accepts a list of alternating keys and their value matchers:

```
hamcrest.library.collection.isdict_containingentries.has_entries(key1,
                                                                    value_matcher1[,
                                                                    ...])
```

Parameters

- **key1** – A key (not a matcher) to look up.
- **valueMatcher1** – The matcher to satisfy for the value, or an expected value for *equal_to* matching.

Examples:

```
has_entries('foo', equal_to(1), 'bar', equal_to(2))
has_entries('foo', 1, 'bar', 2)
```

3.6.2 has_entry

```
class hamcrest.library.collection.isdict_containing.IsDictContaining(key_matcher:
                                                                    ham-
                                                                    crest.core.matcher.Matcher[~K],
                                                                    value_matcher:
                                                                    ham-
                                                                    crest.core.matcher.Matcher[~V])
```

Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_to (*description: hamcrest.core.description.Description*) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters *description* – The description to be built or appended to.

```
hamcrest.library.collection.isdict_containing.has_entry(key_match:
                                                         Union[K,
                                                         ham-
                                                         crest.core.matcher.Matcher[~K][K]],
                                                         value_match:
                                                         Union[V,
                                                         ham-
                                                         crest.core.matcher.Matcher[~V][V]])
                                                         → ham-
                                                         crest.core.matcher.Matcher[typing.Mapping[~K,
                                                         ~V]][Mapping[K, V]]
```

Matches if dictionary contains key-value entry satisfying a given pair of matchers.

Parameters

- **key_match** – The matcher to satisfy for the key, or an expected value for *equal_to* matching.
- **value_match** – The matcher to satisfy for the value, or an expected value for *equal_to* matching.

This matcher iterates the evaluated dictionary, searching for any key-value entry that satisfies *key_match* and *value_match*. If a matching entry is found, *has_entry* is satisfied.

Any argument that is not a matcher is implicitly wrapped in an *equal_to* matcher to check for equality.

Examples:

```
has_entry(equal_to('foo'), equal_to(1))
has_entry('foo', 1)
```

3.6.3 has_key

class hamcrest.library.collection.isdict_containingkey.**IsDictContainingKey** (*key_matcher*: hamcrest.core.matcher.Matcher)

Bases: hamcrest.core.base_matcher.BaseMatcher

describe_to (*description*: hamcrest.core.description.Description) → None

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters *description* – The description to be built or appended to.

hamcrest.library.collection.isdict_containingkey.**has_key** (*key_match*: Union[K, hamcrest.core.matcher.Matcher[~K][K]]) → hamcrest.core.matcher.Matcher[typing.Mapping[~K, typing.Any]][Mapping[K, Any]]

Matches if dictionary contains an entry whose key satisfies a given matcher.

Parameters *key_match* – The matcher to satisfy for the key, or an expected value for *equal_to* matching.

This matcher iterates the evaluated dictionary, searching for any key-value entry whose key satisfies the given matcher. If a matching entry is found, *has_key* is satisfied.

Any argument that is not a matcher is implicitly wrapped in an *equal_to* matcher to check for equality.

Examples:

```
has_key(equal_to('foo'))
has_key('foo')
```

3.6.4 has_value

```
class hamcrest.library.collection.isdict_containingvalue.IsDictContainingValue (value_matcher: hamcrest.core.matcher.Matcher)
```

Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_to (*description: hamcrest.core.description.Description*) → None
Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

```
hamcrest.library.collection.isdict_containingvalue.has_value (value: Union[V, hamcrest.core.matcher.Matcher[~V][V]]) → hamcrest.core.matcher.Matcher[typing.Mapping[~V][Mapping[Any, V]]
```

Matches if dictionary contains an entry whose value satisfies a given matcher.

Parameters **value_match** – The matcher to satisfy for the value, or an expected value for *equal_to* matching.

This matcher iterates the evaluated dictionary, searching for any key-value entry whose value satisfies the given matcher. If a matching entry is found, *has_value* is satisfied.

Any argument that is not a matcher is implicitly wrapped in an *equal_to* matcher to check for equality.

Examples:

```
has_value(equal_to('bar'))
has_value('bar')
```

3.7 Decorator Matchers

Matchers that decorate other matchers for better expression.

3.7.1 described_as

```
class hamcrest.core.core.described_as.DescribedAs (description_template: str, matcher: hamcrest.core.matcher.Matcher[typing.Any][Any], *values)
```

Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_mismatch (*item: Any, mismatch_description: hamcrest.core.description.Description*) → None
Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that *matches(item)* is False, but will not check this.

Parameters

- **item** – The item that the *Matcher* has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to (*description*: *hamcrest.core.description.Description*) → None
Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

matches (*item*: Any, *mismatch_description*: Optional[*hamcrest.core.description.Description*] = None)
→ bool
Evaluates the matcher for argument item.

If a mismatch is detected and argument *mismatch_description* is provided, it will generate a description of why the matcher has not accepted the item.

Parameters

- **item** – The object against which the matcher is evaluated.
- **mismatch_description** –

Returns True if item matches, otherwise False.

hamcrest.core.core.described_as.described_as (*description*, *matcher*[, *value1*[, ...]])
Adds custom failure description to a given matcher.

Parameters

- **description** – Overrides the matcher's description.
- **matcher** – The matcher to satisfy.
- **value1, ..** – Optional comma-separated list of substitution values.

The description may contain substitution placeholders %0, %1, etc. These will be replaced by any values that follow the matcher.

3.7.2 is_

class *hamcrest.core.core.is_.Is* (*matcher*: *hamcrest.core.matcher.Matcher*[~T][T])
Bases: *hamcrest.core.base_matcher.BaseMatcher*

describe_mismatch (*item*: T, *mismatch_description*: *hamcrest.core.description.Description*) → None
Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that *matches* (*item*) is False, but will not check this.

Parameters

- **item** – The item that the *Matcher* has rejected.
- **mismatch_description** – The description to be built or appended to.

describe_to (*description*: *hamcrest.core.description.Description*)
Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters *description* – The description to be built or appended to.

matches (*item*: *T*, *mismatch_description*: *Optional[hamcrest.core.description.Description]* = *None*) → *bool*
Evaluates the matcher for argument *item*.

If a mismatch is detected and argument *mismatch_description* is provided, it will generate a description of why the matcher has not accepted the item.

Parameters

- **item** – The object against which the matcher is evaluated.
- **mismatch_description** –

Returns *True* if *item* matches, otherwise *False*.

`hamcrest.core.core.is_.is_(x)`

Decorates another matcher, or provides shortcuts to the frequently used `is(equal_to(x))` and `is(instance_of(x))`.

Parameters *x* – The matcher to satisfy, or a type for *instance_of* matching, or an expected value for *equal_to* matching.

This matcher compares the evaluated object to the given matcher.

Note: PyHamcrest's `is_` matcher is unrelated to Python's `is` operator. The matcher for object identity is *same_instance*.

If the *x* argument is a matcher, its behavior is retained, but the test may be more expressive. For example:

```
assert_that(value, less_than(5))
assert_that(value, is_(less_than(5)))
```

If the *x* argument is a type, it is wrapped in an *instance_of* matcher. This makes the following statements equivalent:

```
assert_that(cheese, instance_of(Cheddar))
assert_that(cheese, is_(instance_of(Cheddar)))
assert_that(cheese, is_(Cheddar))
```

Otherwise, if the *x* argument is not a matcher, it is wrapped in an *equal_to* matcher. This makes the following statements equivalent:

```
assert_that(cheese, equal_to(smelly))
assert_that(cheese, is_(equal_to(smelly)))
assert_that(cheese, is_(smelly))
```

Choose the style that makes your expression most readable. This will vary depending on context.

Integration with PyUnit and Other Libraries

4.1 `assert_that`

`hamcrest.core.assert_that.assert_that(actual, matcher[, reason])`

Asserts that actual value satisfies matcher. (Can also assert plain boolean condition.)

Parameters

- **actual** – The object to evaluate as the actual value.
- **matcher** – The matcher to satisfy as the expected condition.
- **reason** – Optional explanation to include in failure description.

`assert_that` passes the actual value to the matcher for evaluation. If the matcher is not satisfied, an exception is thrown describing the mismatch.

`assert_that` is designed to integrate well with PyUnit and other unit testing frameworks. The exception raised for an unmet assertion is an `AssertionError`, which PyUnit reports as a test failure.

With a different set of parameters, `assert_that` can also verify a boolean condition:

`hamcrest.core.assert_that.assert_that(assertion[, reason])`

Parameters

- **assertion** – Boolean condition to verify.
- **reason** – Optional explanation to include in failure description.

This is equivalent to the `assertTrue` method of `unittest.TestCase`, but offers greater flexibility in test writing by being a standalone function.

4.2 match_equality

`hamcrest.library.integration.match_equality.match_equality` (*matcher*: *hamcrest.core.matcher.Matcher*)
→ *hamcrest.library.integration.match_equality.Equality*

Wraps a matcher to define equality in terms of satisfying the matcher.

`match_equality` allows Hamcrest matchers to be used in libraries that are not Hamcrest-aware. They might use the equality operator:

```
assert match_equality(matcher) == object
```

Or they might provide a method that uses equality for its test:

```
library.method_that_tests_eq(match_equality(matcher))
```

One concrete example is integrating with the `assert_called_with` methods in Michael Foord's [mock](#) library.

5.1 Helpers

Utilities for writing Matchers

5.1.1 hasmethod

`hamcrest.core.helpers.hasmethod.hasmethod(obj: object, methodname: str) → bool`
Does obj have a method named methodname?

5.1.2 wrap_matcher

`hamcrest.core.helpers.wrap_matcher.wrap_matcher(x: Union[hamcrest.core.matcher.Matcher[~T]][T], T]) → hamcrest.core.matcher.Matcher[~T][T]`

Wraps argument in a matcher, if necessary.

Returns the argument as-is if it is already a matcher, otherwise wrapped in an `equal_to` matcher.

5.2 BaseDescription

class `hamcrest.core.base_description.BaseDescription`
Bases: `hamcrest.core.description.Description`
Base class for all `Description` implementations.
append (*string: str*) → None
Append the string to the description.

append_description_of (*value: Any*) → hamcrest.core.description.Description

Appends description of given value to this description.

If the value implements *describe_to*, then it will be used.

Returns *self*, for chaining

append_list (*start: str, separator: str, end: str, list: Iterable[Any]*) → hamcrest.core.description.Description

Appends a list of objects to the description.

Parameters

- **start** – String that will begin the list description.
- **separator** – String that will separate each object in the description.
- **end** – String that will end the list description.
- **list** – List of objects to be described.

Returns *self*, for chaining

append_text (*text: str*) → hamcrest.core.description.Description

Appends some plain text to the description.

Returns *self*, for chaining

5.3 BaseMatcher

class hamcrest.core.base_matcher.BaseMatcher

Bases: *hamcrest.core.matcher.Matcher*

Base class for all *Matcher* implementations.

Most implementations can just implement *_matches*, leaving the handling of any mismatch description to the *matches* method. But if it makes more sense to generate the mismatch description during the matching, override *matches* instead.

_matches (*item: T*) → bool

describe_match (*item: T, match_description: hamcrest.core.description.Description*) → None

Generates a description of why the matcher has accepted the item.

The description may be part of a larger description of why a matching failed, so it should be concise.

This method assumes that *matches* (*item*) is True, but will not check this.

Parameters

- **item** – The item that the *Matcher* has accepted.
- **match_description** – The description to be built or appended to.

describe_mismatch (*item: T, mismatch_description: hamcrest.core.description.Description*) → None

Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that *matches* (*item*) is False, but will not check this.

Parameters

- **item** – The item that the *Matcher* has rejected.

- **mismatch_description** – The description to be built or appended to.

matches (*item*: *T*, *mismatch_description*: *Optional[hamcrest.core.description.Description]* = *None*) → *bool*
Evaluates the matcher for argument *item*.

If a mismatch is detected and argument *mismatch_description* is provided, it will generate a description of why the matcher has not accepted the item.

Parameters

- **item** – The object against which the matcher is evaluated.
- **mismatch_description** –

Returns *True* if *item* matches, otherwise *False*.

5.4 Description

class `hamcrest.core.description.Description`

Bases: `object`

A description of a *Matcher*.

A *Matcher* will describe itself to a description which can later be used for reporting.

append_description_of (*value*: *Any*) → `hamcrest.core.description.Description`
Appends description of given value to this description.

If the value implements *describe_to*, then it will be used.

Returns *self*, for chaining

append_list (*start*: *str*, *separator*: *str*, *end*: *str*, *list*: *Iterable[Any]*) → `hamcrest.core.description.Description`
Appends a list of objects to the description.

Parameters

- **start** – String that will begin the list description.
- **separator** – String that will separate each object in the description.
- **end** – String that will end the list description.
- **list** – List of objects to be described.

Returns *self*, for chaining

append_text (*text*: *str*) → `hamcrest.core.description.Description`
Appends some plain text to the description.

Returns *self*, for chaining

5.5 Matcher

class `hamcrest.core.matcher.Matcher`

Bases: `typing.Generic`, `hamcrest.core.selfdescribing.SelfDescribing`

A matcher over acceptable values.

A matcher is able to describe itself to give feedback when it fails.

Matcher implementations should *not* directly implement this protocol. Instead, *extend* the `BaseMatcher` class, which will ensure that the `Matcher` API can grow to support new features and remain compatible with all `Matcher` implementations.

describe_match (*item*: *T*, *match_description*: `hamcrest.core.description.Description`) → `None`

Generates a description of why the matcher has accepted the item.

The description may be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches (item)` is `True`, but will not check this.

Parameters

- **item** – The item that the `Matcher` has accepted.
- **match_description** – The description to be built or appended to.

describe_mismatch (*item*: *T*, *mismatch_description*: `hamcrest.core.description.Description`) → `None`

Generates a description of why the matcher has not accepted the item.

The description will be part of a larger description of why a matching failed, so it should be concise.

This method assumes that `matches (item)` is `False`, but will not check this.

Parameters

- **item** – The item that the `Matcher` has rejected.
- **mismatch_description** – The description to be built or appended to.

matches (*item*: *T*, *mismatch_description*: `Optional[hamcrest.core.description.Description]` = `None`) → `bool`

Evaluates the matcher for argument `item`.

If a mismatch is detected and argument `mismatch_description` is provided, it will generate a description of why the matcher has not accepted the item.

Parameters

- **item** – The object against which the matcher is evaluated.
- **mismatch_description** –

Returns `True` if `item` matches, otherwise `False`.

5.6 SelfDescribing

class `hamcrest.core.selfdescribing.SelfDescribing`

Bases: `object`

The ability of an object to describe itself.

describe_to (*description*: `hamcrest.core.description.Description`) → `None`

Generates a description of the object.

The description may be part of a description of a larger object of which this is just a component, so it should be worded appropriately.

Parameters **description** – The description to be built or appended to.

5.7 SelfDescribingValue

class hamcrest.core.selfdescribingvalue.**SelfDescribingValue** (*value: Any*)

Bases: *hamcrest.core.selfdescribing.SelfDescribing*

Wrap any value in a SelfDescribingValue to satisfy the *SelfDescribing* interface.

Deprecated: No need for this class now that *append_description_of* handles any type of value.

describe_to (*description: hamcrest.core.description.Description*) → None

Generates a description of the value.

5.8 StringDescription

class hamcrest.core.string_description.**StringDescription**

Bases: *hamcrest.core.base_description.BaseDescription*

A *Description* that is stored as a string.

append (*string: str*) → None

Append the string to the description.

hamcrest.core.string_description.**tostring** (*selfdescribing: hamcrest.core.selfdescribing.SelfDescribing*) → str

Returns the description of a *SelfDescribing* object as a string.

Parameters **selfdescribing** – The object to be described.

Returns The description of the object.

CHAPTER 6

Indices and tables

- `genindex`
- `modindex`
- `search`

h

`hamcrest.core.assert_that`, 33
`hamcrest.core.base_description`, 35
`hamcrest.core.base_matcher`, 36
`hamcrest.core.core.allof`, 20
`hamcrest.core.core.anyof`, 21
`hamcrest.core.core.described_as`, 30
`hamcrest.core.core.is_`, 31
`hamcrest.core.core.isanything`, 21
`hamcrest.core.core.isequal`, 9
`hamcrest.core.core.isinstanceof`, 12
`hamcrest.core.core.isnone`, 13
`hamcrest.core.core.isnot`, 21
`hamcrest.core.core.issame`, 13
`hamcrest.core.core.raises`, 14
`hamcrest.core.description`, 37
`hamcrest.core.helpers.hasmethod`, 35
`hamcrest.core.helpers.wrap_matcher`, 35
`hamcrest.core.matcher`, 37
`hamcrest.core.selfdescribing`, 38
`hamcrest.core.selfdescribingvalue`, 39
`hamcrest.core.string_description`, 39
`hamcrest.library.collection.is_empty`, 26
`hamcrest.library.collection.isdict_containing`, 28
`hamcrest.library.collection.isdict_containingentries`, 26
`hamcrest.library.collection.isdict_containingkey`, 29
`hamcrest.library.collection.isdict_containingvalue`, 30
`hamcrest.library.collection.isin`, 25
`hamcrest.library.collection.issequence_containing`, 24
`hamcrest.library.collection.issequence_containinginanyorder`, 23
`hamcrest.library.collection.issequence_containinginorder`, 22
`hamcrest.library.collection.issequence_onlycontains`, 25
`hamcrest.library.integration.match_equality`, 34
`hamcrest.library.number.iscloseto`, 15
`hamcrest.library.number.ordering_comparison`, 16
`hamcrest.library.object.haslength`, 9
`hamcrest.library.object.hasproperty`, 11
`hamcrest.library.object.hasstring`, 10
`hamcrest.library.text.isequal_ignoring_case`, 17
`hamcrest.library.text.isequal_ignoring_whitespace`, 18
`hamcrest.library.text.stringcontains`, 17
`hamcrest.library.text.stringcontainsinorder`, 19
`hamcrest.library.text.stringendswith`, 17
`hamcrest.library.text.stringmatches`, 18
`hamcrest.library.text.stringstartswith`, 19

Symbols

`_matches()` (*hamcrest.core.base_matcher.BaseMatcher* method), 36

A

`all_of()` (in module *hamcrest.core.core.allof*), 20

`AllOf` (class in *hamcrest.core.core.allof*), 20

`any_of()` (in module *hamcrest.core.core.anyof*), 21

`AnyOf` (class in *hamcrest.core.core.anyof*), 21

`anything()` (in module *hamcrest.core.core.isanything*), 21

`append()` (*hamcrest.core.base_description.BaseDescription* method), 35

`append()` (*hamcrest.core.string_description.StringDescription* method), 39

`append_description_of()` (*hamcrest.core.base_description.BaseDescription* method), 35

`append_description_of()` (*hamcrest.core.description.Description* method), 37

`append_list()` (*hamcrest.core.base_description.BaseDescription* method), 36

`append_list()` (*hamcrest.core.description.Description* method), 37

`append_text()` (*hamcrest.core.base_description.BaseDescription* method), 36

`append_text()` (*hamcrest.core.description.Description* method), 37

`assert_that()` (in module *hamcrest.core.assert_that*), 33

B

`BaseDescription` (class in *hamcrest.core.base_description*), 35

`BaseMatcher` (class in *hamcrest.core.base_matcher*), 36

C

`calling()` (in module *hamcrest.core.core.raises*), 14

`close_to()` (in module *hamcrest.library.number.isclose_to*), 15

`contains_exactly()` (in module *hamcrest.library.collection.issequence_containing_in_order*), 23

`contains_inanyorder()` (in module *hamcrest.library.collection.issequence_containing_inanyorder*), 24

`contains_string()` (in module *hamcrest.library.text.stringcontains*), 17

D

`describe_keyvalue()` (*hamcrest.library.collection.isdict_containing_entries.IsDictContainingEntries* method), 26

`describe_match()` (*hamcrest.core.base_matcher.BaseMatcher* method), 36

`describe_match()` (*hamcrest.core.core.raises.raises* method), 14

`describe_match()` (*hamcrest.core.matcher.Matcher* method), 38

`describe_mismatch()` (*hamcrest.core.base_matcher.BaseMatcher* method), 36

`describe_mismatch()` (*hamcrest.core.core.allof.AllOf* method), 20

`describe_mismatch()` (*hamcrest.core.core.described_as.DescribedAs* method), 30

`describe_mismatch()` (*hamcrest.core.core.is_is* method), 31

`describe_mismatch()` (*hamcrest.core.core.isnot.IsNot* method), 21

<code>describe_mismatch()</code>	(<code>hamcrest.core.core.issame.IsSame</code> method), 13	<code>describe_to()</code>	(<code>hamcrest.core.selfdescribingvalue.SelfDescribingValue</code> method), 39
<code>describe_mismatch()</code>	(<code>hamcrest.core.core.raises.raises</code> method), 14	<code>describe_to()</code>	(<code>hamcrest.library.collection.is_empty.IsEmpty</code> method), 26
<code>describe_mismatch()</code>	(<code>hamcrest.core.matcher.Matcher</code> method), 38	<code>describe_to()</code>	(<code>hamcrest.library.collection.isdict_containingentries.IsDictContainingEntries</code> method), 28
<code>describe_mismatch()</code>	(<code>hamcrest.library.collection.isdict_containingentries.IsDictContainingEntries</code> method), 27	<code>describe_to()</code>	(<code>hamcrest.library.collection.isdict_containing.IsDictContaining</code> method), 24
<code>describe_mismatch()</code>	(<code>hamcrest.library.collection.issequence_containing.IsSequenceContaining</code> method), 24	<code>describe_to()</code>	(<code>hamcrest.library.collection.isdict_containingentries.IsDictContaining</code> method), 27
<code>describe_mismatch()</code>	(<code>hamcrest.library.collection.issequence_containing.IsSequenceContaining</code> method), 23	<code>describe_to()</code>	(<code>hamcrest.library.collection.isdict_containingentries.IsDictContaining</code> method), 29
<code>describe_mismatch()</code>	(<code>hamcrest.library.collection.issequence_containinginanyorder.IsSequenceContainingInAnyOrder</code> method), 23	<code>describe_to()</code>	(<code>hamcrest.library.collection.isdict_containingkey.IsDictContainingKey</code> method), 30
<code>describe_mismatch()</code>	(<code>hamcrest.library.collection.issequence_containinginorder.IsSequenceContainingInOrder</code> method), 22	<code>describe_to()</code>	(<code>hamcrest.library.collection.isdict_containingvalue.IsDictContainingValue</code> method), 25
<code>describe_mismatch()</code>	(<code>hamcrest.library.number.isclosesto.IsCloseTo</code> method), 15	<code>describe_to()</code>	(<code>hamcrest.library.collection.isin.IsIn</code> method), 25
<code>describe_mismatch()</code>	(<code>hamcrest.library.object.haslength.HasLength</code> method), 9	<code>describe_to()</code>	(<code>hamcrest.library.collection.issequence_containing.IsSequenceContaining</code> method), 24
<code>describe_mismatch()</code>	(<code>hamcrest.library.object.hasproperty.IsObjectWithProperty</code> method), 11	<code>describe_to()</code>	(<code>hamcrest.library.collection.issequence_containing.IsSequenceContaining</code> method), 24
<code>describe_to()</code>	(<code>hamcrest.core.core.allof.AllOf</code> method), 20	<code>describe_to()</code>	(<code>hamcrest.library.collection.issequence_containinginanyorder.IsSequenceContainingInAnyOrder</code> method), 23
<code>describe_to()</code>	(<code>hamcrest.core.core.anyof.AnyOf</code> method), 21	<code>describe_to()</code>	(<code>hamcrest.library.collection.issequence_containinginorder.IsSequenceContainingInOrder</code> method), 22
<code>describe_to()</code>	(<code>hamcrest.core.core.described_as.DescribedAs</code> method), 31	<code>describe_to()</code>	(<code>hamcrest.library.collection.issequence_onlycontaining.IsSequenceOnlyContaining</code> method), 25
<code>describe_to()</code>	(<code>hamcrest.core.core.is_.Is</code> method), 31	<code>describe_to()</code>	(<code>hamcrest.library.number.isclosesto.IsCloseTo</code> method), 15
<code>describe_to()</code>	(<code>hamcrest.core.core.isanything.IsAnything</code> method), 21	<code>describe_to()</code>	(<code>hamcrest.library.number.ordering_comparison.OrderingComparison</code> method), 16
<code>describe_to()</code>	(<code>hamcrest.core.core.isequal.IsEqual</code> method), 9	<code>describe_to()</code>	(<code>hamcrest.library.object.haslength.HasLength</code> method), 10
<code>describe_to()</code>	(<code>hamcrest.core.core.isinstanceof.IsInstanceOf</code> method), 12	<code>describe_to()</code>	(<code>hamcrest.library.object.hasproperty.IsObjectWithProperty</code> method), 11
<code>describe_to()</code>	(<code>hamcrest.core.core.isnone.IsNone</code> method), 13	<code>describe_to()</code>	(<code>hamcrest.library.object.hasstring.HasString</code> method), 10
<code>describe_to()</code>	(<code>hamcrest.core.core.isnot.IsNot</code> method), 21	<code>describe_to()</code>	(<code>hamcrest.library.text.isequal_ignoring_case.IsEqualIgnoringCase</code> method), 17
<code>describe_to()</code>	(<code>hamcrest.core.core.issame.IsSame</code> method), 13		
<code>describe_to()</code>	(<code>hamcrest.core.core.raises.raises</code> method), 14		
<code>describe_to()</code>	(<code>hamcrest.core.selfdescribing.SelfDescribing</code> method), 39		

`describe_to()` (*hamcrest.core.helpers.hasmethod (module), 35*
crest.library.text.isequal_ignoring_whitespace.IsEqualIgnoringWhiteSpace
method), 18 *hamcrest.core.helpers.wrap_matcher (mod-*
`describe_to()` (*hamcrest.core.matcher (module), 37*
crest.library.text.stringcontainsinorder.StringContainsInOrder
method), 19 *hamcrest.core.selfdescribing (module), 38*
`describe_to()` (*hamcrest.core.selfdescribingvalue (mod-*
crest.library.text.stringmatches.StringMatchesPattern
method), 18 *ule), 39*
hamcrest.core.string_description (mod-
`described_as()` (*in module hamcrest.ule), 39*
crest.core.core.described_as), 31 *hamcrest.library.collection.is_empty*
`DescribedAs` (*class in hamcrest (module), 26*
crest.core.core.described_as), 30 *hamcrest.library.collection.isdict_containing*
`Description` (*class in hamcrest.core.description), 37* *(module), 28*
hamcrest.library.collection.isdict_containingentry
E *(module), 26*
`empty()` (*in module hamcrest.library.collection.isdict_containingkey*
crest.library.collection.is_empty), 26 *(module), 29*
`ends_with()` (*in module hamcrest.library.collection.isdict_containingvalue*
crest.library.text.stringendswith), 17 *(module), 30*
`equal_to()` (*in module hamcrest.library.collection.isin (mod-*
crest.library.text.isequal_ignoring_case), 18 *ule), 25*
`equal_to_ignoring_case()` (*in module hamcrest.library.collection.issequence_containing*
crest.library.text.isequal_ignoring_whitespace), 18 *(module), 24*
`equal_to_ignoring_whitespace()` *hamcrest.library.collection.issequence_containingin*
(in module hamcrest.library.collection.issequence_containingin
crest.library.text.isequal_ignoring_whitespace), 18 *(module), 22*
hamcrest.library.collection.issequence_onlycontain
G *(module), 25*
`greater_than()` (*in module hamcrest.library.integration.match_equality*
crest.library.number.ordering_comparison), 16 *(module), 34*
`greater_than_or_equal_to()` (*in module hamcrest.library.number.iscloseto (mod-*
crest.library.number.ordering_comparison), 16 *ule), 15*
hamcrest.library.number.ordering_comparison
H *(module), 16*
`hamcrest.core.assert_that (module), 33` *hamcrest.library.object.haslength (mod-*
`hamcrest.core.base_description (module), 35` *ule), 9*
`hamcrest.core.base_matcher (module), 36` *hamcrest.library.object.hasproperty*
`hamcrest.core.core.allof (module), 20` *(module), 11*
`hamcrest.core.core.anyof (module), 21` *hamcrest.library.object.hasstring (mod-*
`hamcrest.core.core.described_as (module), 30` *ule), 10*
`hamcrest.core.core.is_ (module), 31` *hamcrest.library.text.isequal_ignoring_case*
`hamcrest.core.core.isanything (module), 21` *(module), 17*
`hamcrest.core.core.isequal (module), 9` *hamcrest.library.text.isequal_ignoring_whitespace*
`hamcrest.core.core.isinstanceof (module), 12` *(module), 18*
`hamcrest.core.core.isnone (module), 13` *hamcrest.library.text.stringcontains*
`hamcrest.core.core.isnot (module), 21` *(module), 17*
`hamcrest.core.core.issame (module), 13` *hamcrest.library.text.stringcontainsinorder*
`hamcrest.core.core.raises (module), 14` *(module), 19*
`hamcrest.core.description (module), 37` *hamcrest.library.text.stringendswith*
(module), 17
hamcrest.library.text.stringmatches
(module), 18

[hamcrest.library.text.startswith \(module\), 19](#)
[has_entries\(\) \(in module hamcrest.library.collection.isdict_containingentries\), 27, 28](#)
[has_entry\(\) \(in module hamcrest.library.collection.isdict_containing\), 28](#)
[has_item\(\) \(in module hamcrest.library.collection.issequence_containing\), 25](#)
[has_items\(\) \(in module hamcrest.library.collection.issequence_containing\), 25](#)
[has_key\(\) \(in module hamcrest.library.collection.isdict_containingkey\), 29](#)
[has_length\(\) \(in module hamcrest.library.object.haslength\), 10](#)
[has_properties\(\) \(in module hamcrest.library.object.hasproperty\), 11, 12](#)
[has_property\(\) \(in module hamcrest.library.object.hasproperty\), 12](#)
[has_string\(\) \(in module hamcrest.library.object.hasstring\), 10](#)
[has_value\(\) \(in module hamcrest.library.collection.isdict_containingvalue\), 30](#)
[HasLength \(class in hamcrest.library.object.haslength\), 9](#)
[hasmethod\(\) \(in module hamcrest.core.helpers.hasmethod\), 35](#)
[HasString \(class in hamcrest.library.object.hasstring\), 10](#)

I

[instance_of\(\) \(in module hamcrest.core.core.isinstanceof\), 12](#)
[Is \(class in hamcrest.core.core.is_\), 31](#)
[is_\(\) \(in module hamcrest.core.core.is_\), 32](#)
[is_in\(\) \(in module hamcrest.library.collection.isin\), 25](#)
[is_not\(\) \(in module hamcrest.core.core.isnot\), 22](#)
[IsAnything \(class in hamcrest.core.core.isanything\), 21](#)
[IsCloseTo \(class in hamcrest.library.number.iscloseto\), 15](#)
[IsDictContaining \(class in hamcrest.library.collection.isdict_containing\), 28](#)
[IsDictContainingEntries \(class in hamcrest.library.collection.isdict_containingentries\), 26](#)
[IsDictContainingKey \(class in hamcrest.library.collection.isdict_containingkey\), 29](#)
[IsDictContainingValue \(class in hamcrest.library.collection.isdict_containingvalue\), 30](#)
[IsEmpty \(class in hamcrest.library.collection.is_empty\), 26](#)
[IsEqual \(class in hamcrest.core.core.isequal\), 9](#)
[IsEqualIgnoringCase \(class in hamcrest.library.text.isequal_ignoring_case\), 17](#)
[IsEqualIgnoringWhiteSpace \(class in hamcrest.library.text.isequal_ignoring_whitespace\), 18](#)
[IsIn \(class in hamcrest.library.collection.isin\), 25](#)
[IsInstanceOf \(class in hamcrest.core.core.isinstanceof\), 12](#)
[IsNone \(class in hamcrest.core.core.isnone\), 13](#)
[IsNot \(class in hamcrest.core.core.isnot\), 21](#)
[isnumeric\(\) \(in module hamcrest.library.number.iscloseto\), 16](#)
[IsObjectWithProperty \(class in hamcrest.library.object.hasproperty\), 11](#)
[IsSame \(class in hamcrest.core.core.issame\), 13](#)
[IsSequenceContaining \(class in hamcrest.library.collection.issequence_containing\), 24](#)
[IsSequenceContainingEvery \(class in hamcrest.library.collection.issequence_containing\), 24](#)
[IsSequenceContainingInAnyOrder \(class in hamcrest.library.collection.issequence_containinginanyorder\), 23](#)
[IsSequenceContainingInOrder \(class in hamcrest.library.collection.issequence_containinginorder\), 22](#)
[IsSequenceOnlyContaining \(class in hamcrest.library.collection.issequence_onlycontaining\), 25](#)

L

[less_than\(\) \(in module hamcrest.library.number.ordering_comparison\), 16](#)
[less_than_or_equal_to\(\) \(in module hamcrest.library.number.ordering_comparison\), 16](#)

M

[match_equality\(\) \(in module hamcrest.library.integration.match_equality\), 34](#)

Matcher (class in hamcrest.core.matcher), 37
 matches() (hamcrest.core.base_matcher.BaseMatcher method), 37
 matches() (hamcrest.core.core.allof.AllOf method), 20
 matches() (hamcrest.core.core.described_as.DescribedAs method), 31
 matches() (hamcrest.core.core.is_.Is method), 32
 matches() (hamcrest.core.matcher.Matcher method), 38
 matches() (hamcrest.library.collection.is_empty.IsEmpty method), 26
 matches() (hamcrest.library.collection.isdict_containingentries.IsDictContainingEntries method), 27
 matches() (hamcrest.library.collection.issequence_containinginanyorder.IsSequenceContainingInAnyOrder method), 23
 matches() (hamcrest.library.collection.issequence_containinginorder.IsSequenceContainingInOrder method), 23
 matches_regexp() (in module hamcrest.library.text.stringmatches), 19
 StringDescription (class in hamcrest.core.string_description), 39
 StringEndsWith (class in hamcrest.library.text.stringendswith), 17
 StringMatchesPattern (class in hamcrest.library.text.stringmatches), 18
 StringStartsWith (class in hamcrest.library.text.stringstartswith), 19
 T
 tostring() (in module hamcrest.core.string_description), 39
 W
 wrap_matcher() (in module hamcrest.core.helpers.wrap_matcher), 35

N

none() (in module hamcrest.core.core.isnone), 13
 not_() (in module hamcrest.core.core.isnot), 22
 not_none() (in module hamcrest.core.core.isnone), 13

O

only_contains() (in module hamcrest.library.collection.issequence_onlycontaining), 26
 OrderingComparison (class in hamcrest.library.number.ordering_comparison), 16

R

Raises (class in hamcrest.core.core.raises), 14
 raises() (in module hamcrest.core.core.raises), 14

S

same_instance() (in module hamcrest.core.core.issame), 13
 SelfDescribing (class in hamcrest.core.selfdescribing), 38
 SelfDescribingValue (class in hamcrest.core.selfdescribingvalue), 39
 starts_with() (in module hamcrest.library.text.stringstartswith), 19
 string_contains_in_order() (in module hamcrest.library.text.stringcontainsinorder), 19
 StringContains (class in hamcrest.library.text.stringcontains), 17
 StringContainsInOrder (class in hamcrest.library.text.stringcontainsinorder), 19